

**KHA 18 LTX BL 24 Quick (600211890) Cordless hammer
18V; Cardboard box; with Metabo Quick change chuck**

Order no. 600211890
EAN 4007430320674



Product may differ from image



- Extremely light and compact cordless hammer with integrated extraction interface
- Maximum drill performance, efficiency and service life thanks to brushless technology and high-performance hammer action
- Dust-free drilling with compact dust extraction ISA 18 LTX 24 (accessory)
- Combination hammer with 3 functions: hammer drilling, drilling and chiselling
- Metabo VibraTech (MVT): working, also continuously, in a low-fatigue manner whilst protecting the user's health
- Metabo Quick: fast, tool-free chuck for working with SDS-plus and straight shank drill bits
- Vario Constamatic (VTC) Electronics for drilling jobs in materials requiring customised speeds, which remain almost constant under load
- Double safe thanks to electronic and mechanical safety shutdown when the drill jams
- LED work light for optimum view of the drilling site
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: www.cordless-alliance-systems.com

Technical data

Characteristics

| | |
|-------------------------------------|------------------|
| Battery voltage | 18 V |
| Max. single blow energy (EPTA) | 2.2 J |
| Maximum impact rate | 4500 bpm |
| Drill-Ø concrete with hammer drills | 24 mm / 1 " |
| Drill-Ø masonry with core bits | 68 mm / 2 5/8 " |
| Drill Ø steel | 13 mm / 1/2 " |
| Drill-Ø soft wood | 25 mm / 1 " |
| No-load speed | 0 - 1200 rpm |
| Bit retainer | SDS-plus |
| Weight without battery pack | 2.7 kg / 6 lbs |
| Weight with battery pack | 3.3 kg / 7.3 lbs |

Vibration

| | |
|------------------------------|-----------------------|
| Hammer drilling concrete | 10.5 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Chiseling | 8.6 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |

Noise emission

| | |
|------------------------------|-----------|
| Sound pressure level | 91 dB(A) |
| Sound power level (LwA) | 102 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Hammer chuck for tools with SDS-plus shank end
 Keyless chuck for tools with cylindrical shank
 rubber-coated side handle
 Drilling depth guide
 without battery pack, without charger