

WEQ 1400-125 (600347190) Angle grinder
(220-240 V / 50 - 60 Hz); Cardboard box; with quick-locking nut

Order no. 600347190
EAN 4061792173378



Product may differ from Image



- Robust, universal and economical: ergonomic angle grinder for any application
- Powerful motor with good overload capacity
- Tacho Constamatic (TC) Full-wave Electronics: fast work progress by means of constant speed under load
- Tool free, fast disc change at the touch of a button with the Metabo M-Quick-System
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly - for maximum user safety and swift progress
- Electronic overload protection for long service life
- Electronic soft start and restart protection
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting

Technical data

Characteristics

| | |
|------------------------------|--------------------|
| Disc-Ø | 125 mm // 4.9 " |
| Rated input power | 1400 W |
| Output power | 780 W |
| No-load speed | 11500 rpm |
| Revolutions at rated load | 10500 rpm |
| Torque | 3.3 Nm / 30 in-lbs |
| Spindle thread | M 14 |
| Handle circumference | 194 mm / 7 5/8 " |
| Weight (without power cable) | 2.2 kg / 4.9 lbs |
| Cable length | 4 m / 13 ft |

Vibration

| | |
|------------------------------|----------------------|
| Surface grinding | 7.5 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Grinding with sandpaper | 2.5 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |

Noise emission

| | |
|------------------------------|----------|
| Sound pressure level | 87 dB(A) |
| Sound power level (LwA) | 98 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Guard
Side handle
Inner support flange
M-Quick flange nut