

SB 18 LT BL (602316890) Cordless hammer drill 18V; Cardboard box

Order no. 602316890 EAN 4007430302359



BRUSHLESS MOTOR

- Brushless cordless hammer drill with optimal power for demanding applications
- Unique Metabo brushless motor for quick work progress and highest efficiency when drilling and screwdriving
- High-performance impact mechanism for optimum drilling performance
- Integrated working light to illuminate the contact area
- With handy belt hook and bit case which can be fixed either on the right or left side
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: www.cordless-alliance-systems.com

Note:

The machine shown may differ in equipment and technical details depending on the configuration. Kindly pay attention to the scope of delivery and product description. Accessories are included only if listed in the Scope of delivery.

Characteristics

Battery voltage	18 V
Maximum torque - soft	34 Nm / 301 in-lbs
Maximum torque, hard	75 Nm / 663.8 in-lbs
Adjustable torque	0.7 - 8 Nm // 6 - 71 in-lbs
Drill-Ø masonry	13 mm / 1/2 "
Drill Ø steel	13 mm / 1/2 "
Drill-Ø soft wood	38 mm / 1 1/2 "
No-load speed	0 - 600 / 0 - 2100 rpm
Maximum impact rate	31950 bpm
Chuck capacity	1.5 - 13 mm // 1/16 - 1/2 "
Weight without battery pack	1.2 kg / 2.6 lbs
Weight with battery pack	1.6 kg / 3.5 lbs
Vibration	
Drilling in metal	2.9 m/s²
Uncertainty of measurement K	1.5 m/s ²
Impact drilling concrete	17.3 m/s ²
Uncertainty of measurement K	1.5 m/s²
Noise emission	
Sound pressure level	91 dB(A)
Sound power level (LwA)	102 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Keyless chuck Belt hook and bit case without battery pack, without charger



SSD 18 LT 200 BL (602397850) Cordless Impact Driver 18V; Cardboard box

Order no. 602397850 EAN 4061792217249



BRUSHLESS MOTOR

- Compact cordless impact driver with 1/4" hexagon socket and 200 Nm
- Unique Metabo brushless motor for quick work progress and highest efficiency for any application
- Three speed/torque levels for a varied range of applications
- Integrated work light for illumination of the work area
- Robust die cast aluminium gear housing for optimum heat dissipation and durability
- Handy belt hook, can be fixed either on the right or left side

Note:

The machine shown may differ in equipment and technical details depending on the configuration. Kindly pay attention to the scope of delivery and product description. Accessories are included only if listed in the Scope of delivery.



Characteristics

Battery voltage	18 V	
Max. screw size	M16	
Max. no-load speed	3050 rpm	
Maximum impact rate	3750 bpm	
Maximum torque	200	
Speed/torque levels	3	
Bit retainer	Hexagon recess 1/4" (6.35 mm)	
Weight without battery pack	1.17 kg / 2.6 lbs	
Weight with battery pack	1.57 kg / 3.5 lbs	
Vibration		
Impact screwdriving	14 m/s²	
Uncertainty of measurement K	1.5 m/s²	
Noise emission		
Uncertainty of measurement K	3 dB(A)	

Scope of delivery

Belt Hook

without battery pack, without charger



LiHD Battery pack 18 V - 5.5 Ah (625368000)

Order no. 625368000 EAN 4007430334640



CAS

- LiHD battery packs for ultimate performance and extremely long application with minimal temperature generation
- Intelligent battery management for long-lasting battery packs with a 3 year warranty
- Patented "AIR COOLED" charging technology
- Permanent Electronic Single Cell Protection (ESCP) when charging, for particularly long life.
- Processor-controlled charge and discharge management
- Capacity display with almost no self-discharge
- Capacity display with almost no self-discharge
- Many brands, one battery pack system: This battery pack is compatible with all 18 V machines and chargers of the CAS brands: www.cordless-alliance-system.com



Characteristics

Battery pack voltage	18 V
Battery pack capacity	5.5 Ah
Energy	99 Wh
Weight	980 g



"AIR COOLED" Charger ASC 55, 12-36 V, AUS/NZ (627047000)

Order no. 627047000 EAN 4007430215864



- The universal one: one charger for all slide-on battery packs of all Volt classes (12-36V)
- Patented "AIR COOLED" charging technology for short charging times thanks to cooling the battery pack during the charging cycle
- Optimal communication between battery pack and charger for maximum service life of the battery packs
- 3-year warranty on all Metabo battery packs and chargers irrespective of the number of charging cycles
- Many brands, one battery pack system: charger for charging all battery packs of the CAS brands: www.cordless-alliance-system.com
- "AIR COOLED" function: the patented principle is based on air-cooling the battery pack during the charging process. The battery packs are gently cooled down to the required charging temperature, and then during the charging process are constantly maintained at optimum temperature. With this principle, a higher tool life of the battery packs and up to 30% shorter total charging time can be achieved.



Characteristics

Battery voltage	12 - 36 V
Mains voltage	220 - 240 V
Mains frequency	50 - 60 Hz
Max. charging current	3/4A
Output rating	55 W
Charging time for 18 V/4.0 Ah	80 min
Charging time for 18 V/8.0 Ah	160 min
Weight	582 g / 20.5 oz



metaBOX 165 L for angle grinder (626890000)

Order no. 626890000 EAN 4061792189508



 Product may differ from Image

- Intelligent transport and storage system for mobile working
- Extremely robust and break-proof due to the material and design for maximum resilience
- Optimum protection of machine and accessories against dirt and moisture (IP43)
- Fast and easy stacking and coupling of the boxes in all system widths
- One box in the stack can easily be opened without having to decouple it
- Comfortable front handle for carrying the box near you and extra-wide cover handle (not for 185 XL) to carry several stacked-up boxes
- Numerous tailor-made inserts (accessories) for individual order inside the box
- Clever accessories: Roller board for maximum mobility as well as an adapter plate to secure the boxes in the vehicle
- metaBOX 165 L, suitable for angle grinders up to disc Ø 125 mm

***Note: Accessories are not included.

Characteristics

Dimensions	496 x 296 x 165 mm // 19.53 x 11.66 x 6 1/2 "
Interior dimensions	479 x 268 x 130 mm // 18 3/4 x 10.56 x 5.13 "
Case volume	16.7
Max. load cover	125 kg / 275.6 lbs
Weight	2.29 kg / 5 lbs
Material	ABS