

SB 18 LT BL (602316890) Cordless hammer drill
18V; Cardboard box

Order no. 602316890
EAN 4007430302359



Product may differ from Image



- Brushless cordless hammer drill with optimal power for demanding applications
- Unique Metabo brushless motor for quick work progress and highest efficiency when drilling and screwdriving
- High-performance impact mechanism for optimum drilling performance
- Integrated working light to illuminate the contact area
- With handy belt hook and bit case which can be fixed either on the right or left side
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: www.cordless-alliance-systems.com

Note

*The machine shown may differ in equipment and technical details depending on the configuration.
Kindly pay attention to the scope of delivery and product description.
Accessories are included only if listed in the Scope of delivery.*

Technical data

Characteristics

| | |
|-----------------------------|-----------------------------|
| Battery voltage | 18 V |
| Maximum torque - soft | 34 Nm / 301 in-lbs |
| Maximum torque, hard | 75 Nm / 663.8 in-lbs |
| Adjustable torque | 0.7 - 8 Nm // 6 - 71 in-lbs |
| Drill-Ø masonry | 13 mm / 1/2 " |
| Drill Ø steel | 13 mm / 1/2 " |
| Drill-Ø soft wood | 38 mm / 1 1/2 " |
| No-load speed | 0 - 600 / 0 - 2100 rpm |
| Maximum impact rate | 31950 bpm |
| Chuck capacity | 1.5 - 13 mm // 1/16 - 1/2 " |
| Weight without battery pack | 1.2 kg / 2.6 lbs |
| Weight with battery pack | 1.6 kg / 3.5 lbs |

Vibration

| | |
|------------------------------|-----------------------|
| Drilling in metal | 2.9 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Impact drilling concrete | 17.3 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |

Noise emission

| | |
|------------------------------|-----------|
| Sound pressure level | 91 dB(A) |
| Sound power level (LwA) | 102 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Keyless chuck
Belt hook and bit case
without battery pack, without charger

SSD 18 LT 200 BL (602397850) Cordless Impact Driver
18V; Cardboard box

Order no. 602397850
EAN 4061792217249



Product may differ from Image



- Compact cordless impact driver with 1/4" hexagon socket and 200 Nm
- Unique Metabo brushless motor for quick work progress and highest efficiency for any application
- Three speed/torque levels for a varied range of applications
- Integrated work light for illumination of the work area
- Robust die cast aluminium gear housing for optimum heat dissipation and durability
- Handy belt hook, can be fixed either on the right or left side

Note

*The machine shown may differ in equipment and technical details depending on the configuration.
Kindly pay attention to the scope of delivery and product description.
Accessories are included only if listed in the Scope of delivery.*

Technical data**Characteristics**

| | |
|-----------------------------|-------------------------------|
| Battery voltage | 18 V |
| Max. screw size | M16 |
| Max. no-load speed | 3050 rpm |
| Maximum impact rate | 3750 bpm |
| Maximum torque | 200 |
| Speed/torque levels | 3 |
| Bit retainer | Hexagon recess 1/4" (6.35 mm) |
| Weight without battery pack | 1.17 kg / 2.6 lbs |
| Weight with battery pack | 1.57 kg / 3.5 lbs |

Vibration

| | |
|------------------------------|----------------------|
| Impact screwdriving | 14 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |

Noise emission

| | |
|------------------------------|---------|
| Uncertainty of measurement K | 3 dB(A) |
|------------------------------|---------|

Scope of delivery

Belt Hook
without battery pack, without charger

ULA 14.4-18 LED (600368000) Cordless Portable Lamp
Cardboard box

Order no. 600368000
EAN 4007430242730



Product may differ from Image



- Powerful LED portable lamp for uniform, bright illumination of the working area
- Compact and handy for versatile use
- Lamp head can be tilted and locked in 12 positions
- Robust aluminium die-cast housing for use on construction sites
- Swivelling hook for suspending the lamp
- Operation with all Li-Power and LiHD slide-on 14.4 and 18 Volt battery packs

Note

*The machine shown may differ in equipment and technical details depending on the configuration.
Kindly pay attention to the scope of delivery and product description.
Accessories are included only if listed in the Scope of delivery.*

Technical data**Characteristics**

| | |
|--|--|
| Battery voltage | 14.4 - 18 V |
| Max. luminous flux | 280 lm |
| Max. operation time per battery charge | 14.4 V / 2.0 Ah: 4.5h / 14.4 V / 4.0 Ah: 9h / 18 V / 2.0 Ah: 6.4h / 18 V / 4.0 Ah: 12.7h / 18 V / 5.2 Ah: 16.5h / 18 V / LiHD 3.1: 10h / 18 V / LiHD 5.5: 17.6h / 18 V / LiHD 6.2: 19.8h |
| Weight without battery pack | 0.4 kg / 0.9 lbs |
| Weight with battery pack | 0.8 kg / 1.8 lbs |

Scope of delivery

without battery pack, without charger

LiHD Battery pack 18 V - 5.5 Ah (625368000)

Order no. 625368000

EAN 4007430334640



Product may differ from Image



- LiHD battery packs for ultimate performance and extremely long application with minimal temperature generation
- Intelligent battery management for long-lasting battery packs with a 3 year warranty
- Patented "AIR COOLED" charging technology
- Permanent Electronic Single Cell Protection (ESCP) when charging, for particularly long life.
- Processor-controlled charge and discharge management
- Capacity display with almost no self-discharge
- Capacity display with almost no self-discharge
- Many brands, one battery pack system: This battery pack is compatible with all 18 V machines and chargers of the CAS brands: www.cordless-alliance-system.com

Technical data

Characteristics

| | |
|-----------------------|--------|
| Battery pack voltage | 18 V |
| Battery pack capacity | 5.5 Ah |
| Energy | 99 Wh |
| Weight | 980 g |

"AIR COOLED" Charger ASC 55, 12-36 V, AUS/NZ (627047000)

Order no. 627047000

EAN 4007430215864



Product may differ from Image



- The universal one: one charger for all slide-on battery packs of all Volt classes (12-36V)
- Patented "AIR COOLED" charging technology for short charging times thanks to cooling the battery pack during the charging cycle
- Optimal communication between battery pack and charger for maximum service life of the battery packs
- 3-year warranty on all Metabo battery packs and chargers irrespective of the number of charging cycles
- Many brands, one battery pack system: charger for charging all battery packs of the CAS brands: www.cordless-alliance-system.com
- "AIR COOLED" function: the patented principle is based on air-cooling the battery pack during the charging process. The battery packs are gently cooled down to the required charging temperature, and then during the charging process are constantly maintained at optimum temperature. With this principle, a higher tool life of the battery packs and up to 30% shorter total charging time can be achieved.

Technical data**Characteristics**

| | |
|-------------------------------|-----------------|
| Battery voltage | 12 - 36 V |
| Mains voltage | 220 - 240 V |
| Mains frequency | 50 - 60 Hz |
| Max. charging current | 3 / 4 A |
| Output rating | 55 W |
| Charging time for 18 V/4.0 Ah | 80 min |
| Charging time for 18 V/8.0 Ah | 160 min |
| Weight | 582 g / 20.5 oz |

Tool bag (small) (657006000)

Order no. 657006000

EAN 4007430243706



Product may differ from Image

- The robust and compact Metabo tool bag
- On the inside of the bag there are three bag compartments with hook and loop straps to take two battery packs and one charger
- On the outside there is a spacious pocket with zipper and two other small pockets on the left and right head with hook and loop closure for quick access
- Comfortable side pads and padded shoulder strap
- Three reflective Metabo logos for optimum visibility on the construction site
- Stable, integrated base plate with strips to protect the bag contents
- Material: water-repellent and tear-proof 600D polyester
- Dimensions (lxwxh): 460 mm x 260 mm x 280 mm