

**SB 18 LTX BL I (602360850) Cordless hammer drill**  
**18V; Cardboard box**

Order no. 602360850  
EAN 4061792188174



Product may differ from image



- Brushless hammer drill with maximum power for demanding applications
- Hammer drill function for drilling in masonry
- Selectable "impuls" mode for removal of stubborn screws and for spot-drilling on smooth surfaces
- Precision Stop: electronic torque control with increased precision for precise, delicate working
- Electronic safety shutdown: no kickback if the drill bit stops unexpectedly - for high user safety
- Integrated LED work light with night light function for optimal brightness in the work area
- With handy belt hook and bit case which can be fixed either on the right or left side
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: [www.cordless-alliance-systems.com](http://www.cordless-alliance-systems.com)

**Note**

*The machine shown may differ in equipment and technical details depending on the configuration.  
Kindly pay attention to the scope of delivery and product description.  
Accessories are included only if listed in the Scope of delivery.*

## Technical data

### Characteristics

|                             |                             |
|-----------------------------|-----------------------------|
| Type of battery pack        | Li-Power                    |
| Battery voltage             | 18 V                        |
| Maximum torque - soft       | 65 Nm / 575 ft. lbs         |
| Pulse torque                | 65 Nm / 575 in-lbs          |
| Maximum torque, hard        | 130 Nm / 1151 ft. lbs       |
| Adjustable torque           | 1 - 20 Nm // 9 - 177 in-lbs |
| Drill-Ø masonry             | 16 mm / 5/8 "               |
| Drill Ø steel               | 13 mm / 1/2 "               |
| Drill-Ø soft wood           | 68 mm / 2.68 "              |
| No-load speed               | 0 - 550 / 0 - 2000 rpm      |
| Maximum impact rate         | 38000 bpm                   |
| Chuck capacity              | 1.5 - 13 mm // 1/16 - 1/2 " |
| Weight without battery pack | 1.8 / 4                     |
| Weight with battery pack    | 2.2 kg / 4.9 lbs            |

### Vibration

|                              |                       |
|------------------------------|-----------------------|
| Drilling in metal            | 2.6 m/s <sup>2</sup>  |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup>  |
| Impact drilling concrete     | 16.5 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.7 m/s <sup>2</sup>  |

### Noise emission

|                              |           |
|------------------------------|-----------|
| Sound pressure level         | 92 dB(A)  |
| Sound power level (LwA)      | 103 dB(A) |
| Uncertainty of measurement K | 3 dB(A)   |

## Scope of delivery

Keyless chuck  
Side handle  
Belt hook and bit case

**SSD 18 LTX 200 BL (602396890) Cordless Impact Driver**  
**18V; Cardboard box**

Order no. 602396890  
EAN 4007430330307



Product may differ from Image



- Compact cordless impact driver with 1/4" hexagon recess and 200 Nm, versatile application
- Unique Metabo brushless motor for quick work progress and highest efficiency for any application
- Automatic Power Shift (APS) supports working with self-tapping screws: automatic torque reduction after drilling to prevent overtightening.
- Twelve speed/torque levels for a wide range of applications
- Integrated work light for illumination of the work area
- Robust die cast aluminium gear housing for optimum heat dissipation and durability
- Handy belt hook, can be fixed either on the right or left side
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: [www.cordless-alliance-systems.com](http://www.cordless-alliance-systems.com)

**Note**

*The machine shown may differ in equipment and technical details depending on the configuration.  
Kindly pay attention to the scope of delivery and product description.  
Accessories are included only if listed in the Scope of delivery.*

**Technical data****Characteristics**

|                             |                               |
|-----------------------------|-------------------------------|
| Type of battery pack        | Li-Power                      |
| Battery voltage             | 18 V                          |
| Max. screw size             | M16                           |
| Max. no-load speed          | 2900 rpm                      |
| Maximum impact rate         | 4000 bpm                      |
| Maximum torque              | 200 Nm / 150 ft. lbs          |
| Speed/torque levels         | 12                            |
| Bit retainer                | Hexagon recess 1/4" (6.35 mm) |
| Weight without battery pack | 0.94 kg / 2.1 lbs             |
| Weight with battery pack    | 1.3 kg / 2.9 lbs              |

**Vibration**

|                              |                      |
|------------------------------|----------------------|
| Impact screwdriving          | 9 m/s <sup>2</sup>   |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |

**Noise emission**

|                              |           |
|------------------------------|-----------|
| Sound pressure level         | 94 dB(A)  |
| Sound power level (LwA)      | 105 dB(A) |
| Uncertainty of measurement K | 3 dB(A)   |

**Scope of delivery**

Belt Hook  
without battery pack, without charger

**WB 18 LT BL 11-125 Quick (613054850) Cordless angle grinder**  
**18V; Cardboard box; with brake, quick-locking nut, rotating battery pack**

Order no. 613054850  
EAN 4061792205383



Product may differ from image



- Brushless cordless angle grinder of the new generation: as powerful as a 1,100 Watt mains-powered tool thanks to 40% more power
- Service-free Brushless motor with highest efficiency and maximum handiness
- Fast brake system for highest user safety: Disc stops within 1 second after switching off
- M-Quick System for tool-free disc change at the touch of a button
- Tool-free adjustable guard; twist-proof
- Battery pack can be rotated in 90° steps for best ergonomics in any working position
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly - for maximum user safety
- Electronic overload protection, soft start and restart protection
- Detachable dust protection filter protects motor from coarse particles
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: [www.cordless-alliance-systems.com](http://www.cordless-alliance-systems.com)

**Note**

*The machine shown may differ in equipment and technical details depending on the configuration.  
Kindly pay attention to the scope of delivery and product description.  
Accessories are included only if listed in the Scope of delivery.*

## Technical data

### Characteristics

|                             |                  |
|-----------------------------|------------------|
| Battery voltage             | 18 V             |
| Disc-Ø                      | 125 mm / 5 "     |
| Max. cutting depth          | 27 mm / 1 1/16 " |
| No-load speed               | 10000 rpm        |
| Spindle thread              | M 14             |
| Handle circumference        | 191 mm / 7.52 "  |
| Weight without battery pack | 1.8              |
| Weight with battery pack    | 2.5              |

### Vibration

|                              |                      |
|------------------------------|----------------------|
| Surface grinding             | 8 m/s <sup>2</sup>   |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |
| Grinding with sandpaper      | 2.5 m/s <sup>2</sup> |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |

### Noise emission

|                              |          |
|------------------------------|----------|
| Sound pressure level         | 81 dB(A) |
| Sound power level (LwA)      | 92 dB(A) |
| Uncertainty of measurement K | 3 dB(A)  |

## Scope of delivery

Guard  
 Inner support flange  
 M-Quick flange nut  
 Side handle  
 Dust protection filter  
 without battery pack, without charger

**SSE 18 LTX BL Compact (602366850) Cordless sabre saw**  
**18V; Cardboard box**

Order no. 602366850  
EAN 4061792181281



Product may differ from Image



- Light, extremely handy saw for one or two handed operation
- Especially suitable for working in difficult to reach places
- Unique Metabo brushless motor for quick work progress and highest efficiency for any application
- Variospeed (V) Electronics for working with customised stroke rates for the materials used
- Saw blade rotatable by 180° for working comfortably overhead
- Extended range of application thanks to unique Quick retainer for sabre saw blades and jigsaw blades
- Depth guide can be adjusted without tools for ideal utilisation of the saw blade and diverse applications such as plunge cuts
- Integrated LED work light for optimum illumination of the cutting line
- Wide range of uses thanks to the adapted Metabo saw blade range
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: [www.cordless-alliance-systems.com](http://www.cordless-alliance-systems.com)

**Note**

*The machine shown may differ in equipment and technical details depending on the configuration.  
Kindly pay attention to the scope of delivery and product description.  
Accessories are included only if listed in the Scope of delivery.*

**Technical data****Characteristics**

|                             |                  |
|-----------------------------|------------------|
| Battery voltage             | 18 V             |
| Strokes in idle             | 0 - 3000 rpm     |
| Saw blade stroke            | 16 mm / 0.629 "  |
| Weight without battery pack | 1.4 kg / 3.1 lbs |
| Weight with battery pack    | 1.8 kg / 4 lbs   |

**Vibration**

|                              |                      |
|------------------------------|----------------------|
| Sawing chipboards            | 13 m/s <sup>2</sup>  |
| Uncertainty of measurement K | 2 m/s <sup>2</sup>   |
| Sawing wooden beam           | 15 m/s <sup>2</sup>  |
| Uncertainty of measurement K | 2.5 m/s <sup>2</sup> |

**Noise emission**

|                              |          |
|------------------------------|----------|
| Sound pressure level         | 82 dB(A) |
| Sound power level (LwA)      | 93 dB(A) |
| Uncertainty of measurement K | 5 dB(A)  |

**Scope of delivery**

Sabre saw blade for wood and metal  
without battery pack, without charger



## LiHD Battery pack 18 V - 5.5 Ah (625368000)

Order no. 625368000

EAN 4007430334640



Product may differ from Image



- LiHD battery packs for ultimate performance and extremely long application with minimal temperature generation
- Intelligent battery management for long-lasting battery packs with a 3 year warranty
- Patented "AIR COOLED" charging technology
- Permanent Electronic Single Cell Protection (ESCP) when charging, for particularly long life.
- Processor-controlled charge and discharge management
- Capacity display with almost no self-discharge
- Capacity display with almost no self-discharge
- Many brands, one battery pack system: This battery pack is compatible with all 18 V machines and chargers of the CAS brands: [www.cordless-alliance-system.com](http://www.cordless-alliance-system.com)

**Technical data**

**Characteristics**

|                       |        |
|-----------------------|--------|
| Battery pack voltage  | 18 V   |
| Battery pack capacity | 5.5 Ah |
| Energy                | 99 Wh  |
| Weight                | 980 g  |

## "AIR COOLED" Charger ASC 55, 12-36 V, AUS/NZ (627047000)

Order no. 627047000

EAN 4007430215864



Product may differ from Image



- The universal one: one charger for all slide-on battery packs of all Volt classes (12-36V)
- Patented "AIR COOLED" charging technology for short charging times thanks to cooling the battery pack during the charging cycle
- Optimal communication between battery pack and charger for maximum service life of the battery packs
- 3-year warranty on all Metabo battery packs and chargers irrespective of the number of charging cycles
- Many brands, one battery pack system: charger for charging all battery packs of the CAS brands: [www.cordless-alliance-system.com](http://www.cordless-alliance-system.com)
- "AIR COOLED" function: the patented principle is based on air-cooling the battery pack during the charging process. The battery packs are gently cooled down to the required charging temperature, and then during the charging process are constantly maintained at optimum temperature. With this principle, a higher tool life of the battery packs and up to 30% shorter total charging time can be achieved.

**Technical data****Characteristics**

|                               |                 |
|-------------------------------|-----------------|
| Battery voltage               | 12 - 36 V       |
| Mains voltage                 | 220 - 240 V     |
| Mains frequency               | 50 - 60 Hz      |
| Max. charging current         | 3 / 4 A         |
| Output rating                 | 55 W            |
| Charging time for 18 V/4.0 Ah | 80 min          |
| Charging time for 18 V/8.0 Ah | 160 min         |
| Weight                        | 582 g / 20.5 oz |

## Tool bag (small) (657006000)

Order no. 657006000

EAN 4007430243706



Product may differ from Image

- The robust and compact Metabo tool bag
- On the inside of the bag there are three bag compartments with hook and loop straps to take two battery packs and one charger
- On the outside there is a spacious pocket with zipper and two other small pockets on the left and right head with hook and loop closure for quick access
- Comfortable side pads and padded shoulder strap
- Three reflective Metabo logos for optimum visibility on the construction site
- Stable, integrated base plate with strips to protect the bag contents
- Material: water-repellent and tear-proof 600D polyester
- Dimensions (lxwxh): 460 mm x 260 mm x 280 mm