

**SB 18 LTX BL I (602360850) Cordless hammer drill**  
**18V; Cardboard box**

Order no. 602360850  
EAN 4061792188174



Product may differ from image



- Brushless hammer drill with maximum power for demanding applications
- Hammer drill function for drilling in masonry
- Selectable "impuls" mode for removal of stubborn screws and for spot-drilling on smooth surfaces
- Precision Stop: electronic torque control with increased precision for precise, delicate working
- Electronic safety shutdown: no kickback if the drill bit stops unexpectedly - for high user safety
- Integrated LED work light with night light function for optimal brightness in the work area
- With handy belt hook and bit case which can be fixed either on the right or left side
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: [www.cordless-alliance-systems.com](http://www.cordless-alliance-systems.com)

**Note**

*The machine shown may differ in equipment and technical details depending on the configuration.  
Kindly pay attention to the scope of delivery and product description.  
Accessories are included only if listed in the Scope of delivery.*

## Technical data

### Characteristics

Type of battery pack	Li-Power
Battery voltage	18 V
Maximum torque - soft	65 Nm / 575 ft. lbs
Pulse torque	65 Nm / 575 in-lbs
Maximum torque, hard	130 Nm / 1151 ft. lbs
Adjustable torque	1 - 20 Nm // 9 - 177 in-lbs
Drill-Ø masonry	16 mm / 5/8 "
Drill Ø steel	13 mm / 1/2 "
Drill-Ø soft wood	68 mm / 2.68 "
No-load speed	0 - 550 / 0 - 2000 rpm
Maximum impact rate	38000 bpm
Chuck capacity	1.5 - 13 mm // 1/16 - 1/2 "
Weight without battery pack	1.8 / 4
Weight with battery pack	2.2 kg / 4.9 lbs

### Vibration

Drilling in metal	2.6 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Impact drilling concrete	16.5 m/s <sup>2</sup>
Uncertainty of measurement K	1.7 m/s <sup>2</sup>

### Noise emission

Sound pressure level	92 dB(A)
Sound power level (LwA)	103 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Keyless chuck  
Side handle  
Belt hook and bit case

**KH 18 LTX BL 24 (601713860) Cordless hammer**  
**18V; Plastic Carry Case**

Order no. 601713860  
EAN 4061792218512



Product may differ from image



- Very lightweight, compact cordless hammer with brushless motor for low-fatigue drilling in any working position
- Maximum drill performance, efficiency and service life thanks to brushless technology and high-performance hammer action
- Dust-free drilling with external dust extraction ESA plus
- Combination hammer with 3 functions: hammer drilling, drilling and chiselling
- Metabo VibraTech (MVT): working, also continuously, in a low-fatigue manner whilst protecting the user's health
- Vario-Tacho-Constamatic (VTC)-Full Wave Electronics for work with materials requiring customised speeds, which remain constant under load
- Electronic soft start for precise spot-drilling
- Safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly
- LED work light for optimum view of the drilling site
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: [www.cordless-alliance-systems.com](http://www.cordless-alliance-systems.com)

**Note**

*The machine shown may differ in equipment and technical details depending on the configuration.  
Kindly pay attention to the scope of delivery and product description.  
Accessories are included only if listed in the Scope of delivery.*

## Technical data

### Characteristics

Battery voltage	18 V
Max. single blow energy (EPTA)	2.2 J
Maximum impact rate	4750 bpm
Drill-Ø concrete with hammer drills	24 mm / 1 "
Drill-Ø masonry with core bits	82 mm / 3 7/32 "
Drill Ø steel	13 mm / 1/2 "
Drill-Ø soft wood	30 mm / 1 3/16 "
No-load speed	0 - 1280 rpm
Bit retainer	SDS-plus
Weight without battery pack	2.7 kg / 5.95 lbs

### Vibration

Hammer drilling concrete	13.6 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Chiseling	9.2 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>

### Noise emission

Sound pressure level	90 dB(A)
Sound power level (LWA)	101 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

rubber-coated side handle  
without battery pack, without charger  
Drilling depth guide  
Plastic carry case

**SSW 18 LTX 300 BL (602395890) Cordless impact wrench**  
**18V; Cardboard box**

Order no. 602395890  
EAN 4007430331892



Product may differ from Image



- Compact cordless impact driver with 1/2" male square and 300 Nm, versatile application
- Unique Metabo brushless motor for quick work progress and highest efficiency for any application
- Automatic Power Shift (APS) supports working with self-tapping screws: automatic torque reduction after drilling to prevent overtightening.
- Low kick-back operation with extremely high torque
- Twelve speed/torque levels for a wide range of applications
- Integrated work light for illumination of the work area
- Robust die cast aluminium gear housing for optimum heat dissipation and durability
- Handy belt hook, can be fixed either on the right or left side
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: [www.cordless-alliance-systems.com](http://www.cordless-alliance-systems.com)

**Note**

*The machine shown may differ in equipment and technical details depending on the configuration.  
Kindly pay attention to the scope of delivery and product description.  
Accessories are included only if listed in the Scope of delivery.*

**Technical data****Characteristics**

Battery voltage	18 V
Max. screw size	M18
Max. no-load speed	0 - 2650 rpm
Maximum impact rate	3750 bpm
Maximum torque	300 Nm / 220 ft. lbs
Max. loosening torque	480 Nm / 355 ft. lbs
Speed/torque levels	12
Bit retainer	Male square 1/2" (12.70 mm)
Weight without battery pack	1.1 kg / 2.4 lbs
Weight with battery pack	1.7 kg / 3.7 lbs

**Vibration**

Impact screwdriving	7 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>

**Noise emission**

Sound pressure level	95 dB(A)
Sound power level (LwA)	106 dB(A)
Uncertainty of measurement K	3 dB(A)

**Scope of delivery**

Belt Hook  
without battery pack, without charger

**WB 18 LT BL 11-125 Quick (613054850) Cordless angle grinder**  
**18V; Cardboard box; with brake, quick-locking nut, rotating battery pack**

Order no. 613054850  
EAN 4061792205383



Product may differ from image



- Brushless cordless angle grinder of the new generation: as powerful as a 1,100 Watt mains-powered tool thanks to 40% more power
- Service-free Brushless motor with highest efficiency and maximum handiness
- Fast brake system for highest user safety: Disc stops within 1 second after switching off
- M-Quick System for tool-free disc change at the touch of a button
- Tool-free adjustable guard; twist-proof
- Battery pack can be rotated in 90° steps for best ergonomics in any working position
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly - for maximum user safety
- Electronic overload protection, soft start and restart protection
- Detachable dust protection filter protects motor from coarse particles
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: [www.cordless-alliance-systems.com](http://www.cordless-alliance-systems.com)

**Note**

*The machine shown may differ in equipment and technical details depending on the configuration.  
Kindly pay attention to the scope of delivery and product description.  
Accessories are included only if listed in the Scope of delivery.*

## Technical data

### Characteristics

Battery voltage	18 V
Disc-Ø	125 mm / 5 "
Max. cutting depth	27 mm / 1 1/16 "
No-load speed	10000 rpm
Spindle thread	M 14
Handle circumference	191 mm / 7.52 "
Weight without battery pack	1.8
Weight with battery pack	2.5

### Vibration

Surface grinding	8 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Grinding with sandpaper	2.5 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>

### Noise emission

Sound pressure level	81 dB(A)
Sound power level (LwA)	92 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Guard  
Inner support flange  
M-Quick flange nut  
Side handle  
Dust protection filter  
without battery pack, without charger



**SSE 18 LTX BL Compact (602366850) Cordless sabre saw  
18V; Cardboard box**

Order no. 602366850  
EAN 4061792181281



Product may differ from Image



- Light, extremely handy saw for one or two handed operation
- Especially suitable for working in difficult to reach places
- Unique Metabo brushless motor for quick work progress and highest efficiency for any application
- Variospeed (V) Electronics for working with customised stroke rates for the materials used
- Saw blade rotatable by 180° for working comfortably overhead
- Extended range of application thanks to unique Quick retainer for sabre saw blades and jigsaw blades
- Depth guide can be adjusted without tools for ideal utilisation of the saw blade and diverse applications such as plunge cuts
- Integrated LED work light for optimum illumination of the cutting line
- Wide range of uses thanks to the adapted Metabo saw blade range
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: [www.cordless-alliance-systems.com](http://www.cordless-alliance-systems.com)

**Note**

*The machine shown may differ in equipment and technical details depending on the configuration.  
Kindly pay attention to the scope of delivery and product description.  
Accessories are included only if listed in the Scope of delivery.*

**Technical data****Characteristics**

Battery voltage	18 V
Strokes in idle	0 - 3000 rpm
Saw blade stroke	16 mm / 0.629 "
Weight without battery pack	1.4 kg / 3.1 lbs
Weight with battery pack	1.8 kg / 4 lbs

**Vibration**

Sawing chipboards	13 m/s <sup>2</sup>
Uncertainty of measurement K	2 m/s <sup>2</sup>
Sawing wooden beam	15 m/s <sup>2</sup>
Uncertainty of measurement K	2.5 m/s <sup>2</sup>

**Noise emission**

Sound pressure level	82 dB(A)
Sound power level (LwA)	93 dB(A)
Uncertainty of measurement K	5 dB(A)

**Scope of delivery**

Sabre saw blade for wood and metal  
without battery pack, without charger

**AG 18 (602242850) Cordless blower**  
**18V; Cardboard box**

Order no. 602242850  
EAN 4007430286901



Product may differ from Image



- Lightweight cordless blower e.g. for blowing off chips from workpieces, workplace, transporter etc.
- Good ergonomics provided by a rubberised handle and an optimum centre of gravity
- Robust design suitable for applications in the workshop and on the construction site
- Vario (V)-Electronics for continuously selectable blowing air velocity rate
- Thumbwheel for preselection of 3 air velocity rate settings for varied output
- Rubberised end piece of the blow tube to protect delicate surfaces
- Comfortable blowing of floor areas using the supplied extension of the blow tube
- Operation with all Li-Power and LiHD slide-on 18 Volt battery packs
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: [www.cordless-alliance-systems.com](http://www.cordless-alliance-systems.com)

**Note**

*The machine shown may differ in equipment and technical details depending on the configuration.  
Kindly pay attention to the scope of delivery and product description.  
Accessories are included only if listed in the Scope of delivery.*

**Technical data****Characteristics**

Battery voltage	18 V
Air volume	1 / 1.55 / 2.6 m <sup>3</sup> /min // 31 / 54 / 91 cfm
Max. air velocity	74 m/s / 166 mph
Weight without battery pack	1.4 kg / 3.1 lbs
Weight with battery pack	1.8 kg / 4 lbs

**Vibration**

Vibration	2.5 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>

**Noise emission**

Sound pressure level	79 dB(A)
Sound power level (LwA)	90 dB(A)
Uncertainty of measurement K	3 dB(A)

**Scope of delivery**

without battery pack, without charger

## LiHD Battery pack 18 V - 5.5 Ah (625368000)

Order no. 625368000

EAN 4007430334640



Product may differ from Image



- LiHD battery packs for ultimate performance and extremely long application with minimal temperature generation
- Intelligent battery management for long-lasting battery packs with a 3 year warranty
- Patented "AIR COOLED" charging technology
- Permanent Electronic Single Cell Protection (ESCP) when charging, for particularly long life.
- Processor-controlled charge and discharge management
- Capacity display with almost no self-discharge
- Capacity display with almost no self-discharge
- Many brands, one battery pack system: This battery pack is compatible with all 18 V machines and chargers of the CAS brands: [www.cordless-alliance-system.com](http://www.cordless-alliance-system.com)

**Technical data**

**Characteristics**

Battery pack voltage	18 V
Battery pack capacity	5.5 Ah
Energy	99 Wh
Weight	980 g

## "AIR COOLED" Charger ASC 55, 12-36 V, AUS/NZ (627047000)

Order no. 627047000

EAN 4007430215864



Product may differ from Image



- The universal one: one charger for all slide-on battery packs of all Volt classes (12-36V)
- Patented "AIR COOLED" charging technology for short charging times thanks to cooling the battery pack during the charging cycle
- Optimal communication between battery pack and charger for maximum service life of the battery packs
- 3-year warranty on all Metabo battery packs and chargers irrespective of the number of charging cycles
- Many brands, one battery pack system: charger for charging all battery packs of the CAS brands: [www.cordless-alliance-system.com](http://www.cordless-alliance-system.com)
- "AIR COOLED" function: the patented principle is based on air-cooling the battery pack during the charging process. The battery packs are gently cooled down to the required charging temperature, and then during the charging process are constantly maintained at optimum temperature. With this principle, a higher tool life of the battery packs and up to 30% shorter total charging time can be achieved.

**Technical data****Characteristics**

Battery voltage	12 - 36 V
Mains voltage	220 - 240 V
Mains frequency	50 - 60 Hz
Max. charging current	3 / 4 A
Output rating	55 W
Charging time for 18 V/4.0 Ah	80 min
Charging time for 18 V/8.0 Ah	160 min
Weight	582 g / 20.5 oz



## Tool bag (large) (657007000)

Order no. 657007000

EAN 4007430243713



Product may differ from Image

- The large, practical Metabo tool bag
- On the inside of the bag there are five bag compartments with hook and loop straps to take three battery packs, one charger and accessories
- On the outside there are two spacious pockets with zipper and three other small pockets for quick access
- Comfortable side pads and padded shoulder strap
- Three reflective Metabo logos for optimum visibility on the construction site
- Stable, integrated base plate with strips to protect the bag contents
- Material: water-repellent and tear-proof 600D polyester
- Dimensions (l x w x h): 670 mm x 290 mm x 325 mm