

## WPBA 18 LTX BL 15-180 Quick DS (601746840) Cordless angle grinder 18V; metaBOX 165 L; with brake, quick-locking nut, rotating battery pack, deadman switch

Order no. 601746840 EAN 4061792246683



Product may differ from Image























- Brushless cordless angle grinder of the new generation: the most powerful one in its class, as powerful as a 1,500 Watt mains-powered tool
- Service-free Brushless motor with highest efficiency and maximum handiness
- Paddle switch with dead man function: safe to operate due to an ergonomically integrated switch
- Fast brake system for highest user safety: Disc stops within 1.5 seconds after switching off
- Best anti-vibration system: integrated auto-balancer for less hand-arm vibrations, longer service life of the machine and up to twice the service life of the grinding wheels
- M-Quick System for tool-free disc change at the touch of a button
- Safety bracket DS for the attachment of a tool safety strap when working at great heights
- Tool-free adjustable guard; twist-proof
- Battery pack can be rotated in 90° steps for best ergonomics in any working position
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly for maximum user safety
- Electronic overload protection, soft start and restart protection
- Detachable dust protection filter protects motor from coarse particles
- With metaBOX, the intelligent solution for transport and storage
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: www.cordless-alliance-systems.com

www.metabo.com 1/2



Technical data	
Characteristics	
Battery voltage	18 V
Disc-Ø	180 mm / 7 "
Max. cutting depth	60 / 2.362
No-load speed	7500 rpm
Spindle thread	M 14
Handle circumference	166
Weight without battery pack	2.4
Weight with battery pack	3.1
Vibration	
Surface grinding	5.24 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Grinding with sandpaper	3 m/s²
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Noise emission	
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Guard

Metabo VibraTech (MVT) side handle

Dust protection filter

Safety bracket DS

metaBOX 165 L

without battery pack, without charger

Inner support flange

M-Quick flange nut

www.metabo.com 2 / 2