

Product Specifications Sheet

B30 Series B-569 Low-Halide Polyester 101.6mm x 30.48m Red



Part No

117973

Hi-Performance Polyester Tape (B-569) has low halide content and is designed for marking stainless steel pipes particularly in harsh environments.

- Durable, ultra-smooth polyester labels with permanent pressure sensitive acrylic adhesive
- Outdoor grade polyester tape can be thermal transfer printed
- Withstands mild chemicals, oil and water
- Enables printers with XY cutters to cut custom shapes or multiple labels out of a single continuous roll
- A ribbon is required to print this material. Use Part Number B30-R10000-WT

Overview

Hi-Performance Polyester Tape (B-569) has low halide content and is designed for marking stainless steel pipes particularly in harsh environments. For use with BBP®31, BBP®33, BBP®35, BBP®37, BradyPrinter i3300, and BradyPrinter S3100.

Specification

	1
Colour	Red
Brand Name	Brady®
Sold	Cartridge of 30 m
Industry	Beverage processing, Buildings identification, Chemical, Education, Energy utilities, Food processing, Covernment, Healthcare, Manufacturing, Oil & gas, Process, Tourism & recreation, Warehouse & logistics, Construction, Maritime, Mining, Pulp & paper
Finish	Closs
Barcode	75447321057
Material	Polyester
Surface	For smooth surfaces
Label Properties	Permanent Adhesive, Harsh Environment, Aggressive Adhesive
Maximum Service Temperature (°C)	100 °C
Minimum Service Temperature (°C)	-40 °C
Adhesive Type	Permanent Acrylic
Print Technology	Thermal Transfer
Performance Characteristics	Abrasion resistance
Resistance Properties	Abrasion-Resistant, Chemical-Resistant
Application	Facility Identification, Pipe and Valve Marking
Printer and Label Applications	General Identification, Inspection Repair, Lean / 5S, Safety, Pipe Marker, Hazardous Materials
Indoor or Outdoor Use	Outdoor Use

Width (mm)	101.60 mm
Overall Dimension	101.60 mm (W) x 30.48 m (L)
Thickness (metric) (mm)	0.076 mm
Label/Tape Dimension	101.60 mm (W) x 30.48 m (L)
Roll Length (m)	30.48 m
Roll Width (mm)	101.60 mm
Quantity per Row	1
Web Width (mm)	107.95 mm
Recommended Ribbon Series	R10000
Recommended Ribbon	B30-R10000-WT
Printer Compatibility	<u>BBP35</u> , <u>BBP37</u> , <u>S3100</u> , BBP31, <u>i300</u> , BBP33, <u>S3700</u> , BBP30, S3000, i5300
Continuous or Die-cut	Continuous

Providing a range of Identification Solutions & Services throughout Australia and Worldwide © Copyright 2023 Brady Worldwide Inc. Prices are suggested only & exclude GST. *MSRP (Manufacturer's Suggested Retail Price).