

Product Specifications Sheet

B30 Series B-569 Low-Halide Polyester 101.6mm x 30.48m Yellow



Part No

117990

Hi-Performance Polyester Tape (B-569) has low halide content and is designed for marking stainless steel pipes particularly in harsh environments.

- Durable, ultra-smooth polyester labels with permanent pressure sensitive acrylic adhesive
- Outdoor grade polyester tape can be thermal transfer printed
- Withstands mild chemicals, oil and water
- Enables printers with XY cutters to cut custom shapes or multiple labels out of a single continuous roll
- A ribbon is required to print this material. Use Part Number B30-R10000

Overview

Hi-Performance Polyester Tape (B-569) has low halide content and is designed for marking stainless steel pipes particularly in harsh environments. For use with BBP®31, BBP®33, BBP®35, BBP®37, BradyPrinter i3300, and BradyPrinter S3100.

Specification

| Colour | Yellow |
|----------------------------------|---|
| Brand Name | Brady® |
| Sold | Cartridge of 30 m |
| Industry | Beverage processing, Buildings identification, Chemical, Education, Energy utilities, Food processing, Government, Healthcare, Manufacturing, Oil & gas, Process, Tourism & recreation, Warehouse & logistics, Construction, Maritime, Mining, Pulp & paper |
| Finish | Gloss |
| Barcode | 75447321074 |
| Material | Polyester |
| Surface | For smooth surfaces |
| Label Properties | Permanent Adhesive, Harsh Environment, Aggressive Adhesive |
| Maximum Service Temperature (°C) | 100 °C |
| Minimum Service Temperature (°C) | -40 °C |
| Adhesive Type | Permanent Acrylic |
| Print Technology | Thermal Transfer |
| Performance Characteristics | Abrasion resistance |
| Resistance Properties | Abrasion-Resistant, Chemical-Resistant |
| Application | Facility Identification, Pipe and Valve Marking |
| Printer and Label Applications | General Identification, Inspection Repair, Lean / 5S, Safety, Pipe Marker, Hazardous Materials |
| Indoor or Outdoor Use | Outdoor Use |

| Width (mm) | 101.60 mm |
|---------------------------|---|
| Overall Dimension | 101.60 mm (W) x 30.48 m (L) |
| Thickness (metric) (mm) | 0.076 mm |
| Label/Tape Dimension | 101.60 mm (W) x 30.48 m (L) |
| Roll Length (m) | 30.48 m |
| Roll Width (mm) | 101.60 mm |
| Quantity per Row | 1 |
| Web Width (mm) | 107.95 mm |
| Recommended Ribbon Series | R10000 |
| Recommended Ribbon | B30-R10000 |
| Printer Compatibility | <u>BBP35</u> , <u>BBP37</u> , <u>S3100</u> , BBP31, <u>i300</u> , BBP33, <u>S3700</u> , BBP30, S3000, i5300 |
| Continuous or Die-cut | Continuous |

Providing a range of Identification Solutions & Services throughout Australia and Worldwide © Copyright 2023 Brady Worldwide Inc. Prices are suggested only & exclude GST. *MSRP (Manufacturer's Suggested Retail Price).